



# U-PLEX<sup>®</sup> Linker Set

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 26Jul2018

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** U-PLEX Linker Set: 2-Assay, 3-Assay, 4-Assay, 5-Assay, 6-Assay, 7-Assay, 8-Assay, 9-Assay and 10-Assay

**Product Code:** 3-2000-42001\*, 3-2000-42002\*, 3-2000-42003\*

### 1.2. Intended Use of the Product

Laboratory chemicals

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Meso Scale Diagnostics

1601 Research Blvd

Rockville, MD 20850-3128

T 240-314-2600

### 1.4. Emergency Telephone Number

**Emergency Number** : Within the U.S. and Canada (24 hours, toll-free)

CHEMTREC: 1-800-424-9300

**International (Hours of operation: Monday – Friday, 1230 – 2130 UTC or 0830 – 1730 ET)**

MSD direct dial: +1-240-314-2799

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

**GHS-US classification**

Not classified

### 2.2. Label Elements

**GHS-US Labeling**

No labeling applicable

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US) No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product Identifier	% (w/w)	GHS-US classification
Sodium azide	(CAS No) 26628-22-8	<= 0.05	Acute Tox. 2 (Oral), H300 Acute Tox. 1 (Dermal), H310 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

# U-PLEX® Linker Set

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Not expected to present a significant hazard under anticipated conditions of normal use.

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** Prolonged exposure may cause skin irritation.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None known.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, dry chemical, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all unnecessary exposure.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal.

### 6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

# U-PLEX® Linker Set

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Laboratory chemicals

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Sodium azide (26628-22-8)		
USA ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
USA ACGIH	ACGIH Ceiling (ppm)	0.11 ppm (vapor)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	0.1 ppm
Alberta	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Alberta	OEL Ceiling (ppm)	0.11 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
British Columbia	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
British Columbia	OEL Ceiling (ppm)	0.11 ppm
Manitoba	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Manitoba	OEL Ceiling (ppm)	0.11 ppm (vapor)
New Brunswick	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
New Brunswick	OEL Ceiling (ppm)	0.11 ppm (vapor)
Newfoundland & Labrador	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL Ceiling (ppm)	0.11 ppm (vapor)
Nova Scotia	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Nova Scotia	OEL Ceiling (ppm)	0.11 ppm (vapor)
Nunavut	OEL Ceiling (mg/m <sup>3</sup> )	0.27 mg/m <sup>3</sup>
Nunavut	OEL Ceiling (ppm)	0.1 ppm
Northwest Territories	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Northwest Territories	OEL Ceiling (ppm)	0.11 ppm
Ontario	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Ontario	OEL Ceiling (ppm)	0.11 ppm
Prince Edward Island	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Prince Edward Island	OEL Ceiling (ppm)	0.11 ppm (vapor)
Québec	PLAFOND (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Québec	PLAFOND (ppm)	0.11 ppm
Saskatchewan	OEL Ceiling (mg/m <sup>3</sup> )	0.29 mg/m <sup>3</sup>
Saskatchewan	OEL Ceiling (ppm)	0.11 ppm
Yukon	OEL Ceiling (mg/m <sup>3</sup> )	0.3 mg/m <sup>3</sup>
Yukon	OEL Ceiling (ppm)	0.1 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

# U-PLEX® Linker Set

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** None known.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

- Acute Toxicity:** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Not classified.
- Serious Eye Damage/Irritation:** Not classified.
- Respiratory or Skin Sensitization:** Not classified
- Germ Cell Mutagenicity:** Not classified
- Teratogenicity:** Not classified

# U-PLEX® Linker Set

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None known.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Sodium azide (26628-22-8)	
LD50 Oral Rat	27 mg/kg
LD50 Dermal Rabbit	20 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Not classified.

Sodium azide (26628-22-8)	
LC50 Fish 1	0.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC 50 Fish 2	0.7 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
ErC50 (algae)	0.348 mg/l

**12.2. Persistence and Degradability** Not established

**12.3. Bioaccumulative Potential** Not established

**12.4. Mobility in Soil** Not available

**12.5. Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Ecology – Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

**14.1. In Accordance with DOT** Not regulated for transport

**14.2. In Accordance with IMDG** Not regulated for transport

**14.3. In Accordance with IATA** Not regulated for transport

**14.4. In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

Sodium azide (26628-22-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500 (This material is a reactive solid. The TPQ does not default to 10000 pounds for non-powder, non-molten, non-solution form)
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

### 15.2. US State Regulations

